



TECHNICAL DATA:

- **Internal parts:** stainless steel
- **Seals:** NBR
- **Fluid temperature:** -10°C to +60°C
- **Ambient temperature:** max +50°C
- **Voltage:** 230, 115, 48, 24 V AC / 24, 12 V DC (Types PV and PVNC 230 V AC only)
- **Electrical protection:** IP65 (with plug to ISO 4400)
Long term use in humid environment requires the use of sealing sets.

Closed when de-energised (NC) DIRECT ACTING (fig. 1) EN 161 Certified

Closed when de-energised (NC) DIRECT ACTING (fig. 2) EN 161 Certified

Closed when de-energised (NC) GAS LINE SHUTOFF (fig. 3) EN 161 Certified

Open when de-energised (NO) GAS LINE SHUTOFF (fig. 4) EN 161 Certified

Closed when de-energised (NC) FOR GAS CYLINDERS (fig. 5) EN 161 Certified

Closed when de-energised (NC) PROCESS VALVES (fig. 6) EN 161 Certified

Ports	Orifice size [mm]	Kv (air at 1 bar) [m ³ /h]	Differential pressure [mbar]		Body	Seal	Mass [kg]	Coil type	Model	Order code
			min	max						
G3/4	18	290	0	1000	Brass	NBR	0.8	TM35	M2521	301697
G1	25	660	0	1000	Brass	NBR	1.2	TM35	M2621	301698
G6/4	40	1230	0	1000	Brass	NBR	2.75	TM40	M275	370810
G2	50	2268	0	1000	Brass	NBR	5.9	TM40	M282	391491

EN 161 Certificate of Conformity

OPTIONS:

- EEx me II explosionproof coils
- Other versions on request.