


TECHNICAL DATA:

- **Internal parts:** stainless steel
 - **Seals:** EPDM, PTFE
 - **Ambient temperature:** max +55°C
 - **Voltage:** 230, 115, 48, 24 V AC / 24, 12 V DC
 - **Duty cycle:** continuous (ED100%)
 - **Electrical protection:** IP65
(with plug to ISO 4400)
- Long term use in humid environment requires the use of sealing sets.

Ports	Orifice size [mm]	Kv (water 1bar) [l/min]	Differential pressure [bar]		Fluid temperature max [°C]	Body	Seal	Mass [kg]	Coil type	Model	Order code	Fig.
			min	max								
2/2 direct acting, closed when de-energised (NC)												
G1/4	2	1.8	0	10	180	Brass	PTFE	0.35	TM30	D224	320365	-
	2.3	2	0	8	180	Brass	EPDM	0.25	TM30	D224	320511	1
	2.3	2	0	8	180	Brass	EPDM	0.49	TM35	DP24	320490	
	3	3.2	0	8	180	Brass	PTFE	0.35	TM30	D222	320312	-
	4.5	7.5	0	6	180	Brass	EPDM	0.49	TM35	DP25	320491	1
2/2 diaphragm - pilot operated, closed when de-energised (NC)												
G1/2	10	20	0.5	9	180	Brass	PTFE	0.49	TM30	M246	340610	3
G1	18.5	155	0.5	9	180	Brass	PTFE	1.32	TM30	M263	360514	2
G6/4	40	350	0.35	10	180	Brass	PTFE	3.25	TM35	B26	316714	
G2	50	630	0.5	10	180	Brass	PTFE	5.45	TM35	B26	316718	
2/2 diaphragm, low pressure steam, closed when de-energised (NC)												
G1/2	12	40	0	10	130	Brass	EPDM	0.43	TM30	M2451	301703	3
G3/4	18	65	0	10	130	Brass	EPDM	0.46	TM35	M2521	301706	
G1	25	180	0	10	130	Brass	EPDM	1.2	TM35	M2621	301710	
G6/4	40	330	0	1	130	Brass	EPDM	2.75	TM40	M275	370811	
3/2 direct acting, closed when de-energised (NC)												
G1/4	1.8	1.5	0	10	165	Brass	EPDM	0.31	TM30	D321	330519	5
FL32	1.5	1.4	0	10	165	Brass	EPDM	0.23	TM30	D382	330515	6
2/2 pressure operated piston valves, closed when de-pressurised (NC)												4

OPTIONS:

- EEx me II explosionproof coils
- Other versions on request.